



IVR 16CH 2 HDD SUPPORT UPTO 4K H.265+

Features

- ◆ Support the classification of face recognition black and white lists and triggers various linkage alarm
- ◆ Support to search for pictures and video files by face
- ◆ H.265+/H.265/H.264 dual stream decoding
- ◆ Support synchronous recording, remote monitoring, backup; up to 16CH video synchronous playback and multi-channel backward playback
- ◆ Support 30min instant playback
- ◆ Support Two-way audio intercom
- ◆ Support standard ONVIF, SLINK, RTSP protocol
- ◆ Support IE, mobile phone APP, VMS monitoring
- ◆ Support Smart IPC: Target Count, Object Left/Lost, Electric Fence, Line Crossing, Face Grouping List, Face Detection, Humanoid Detection, Retrograde Detection, Leave Position Detection
- ◆ Support IPC centralized management, including IPC parameter configuration, information export and import, real-time information acquisition and upgrade, etc.
- ◆ Support offline collection
- ◆ Support disk grouping quotas and disk group storage modes



Product code	T38017
Operating System	Embedded Linux
User Interface	GUI
Video Compression	H.264/H.265/H.265+
Video Resolution	4K\5MP\3MP\2MP
Smart Features	Target Count, Object Left/Lost, Electronic Fence, Line Crossing, Face Grouping List, Face Detection, Humanoid Detection, Retrograde Detection, Leave Position Detection (need front end IPC supported)
Video Input	16CH Digital (2592X1944) + 16CH Preview + 9CH Playback
HDMI output	1 CH, Resolution : 1920x1080/60Hz
VGA output	1 CH, Resolution: 1920x1080P/60Hz
Decode Playback	16ch At same time Playback
Recording Mode	Timing recording or alarm recording, Timing record, Alarm recorder, Stop record
Playback Mode	On time playback, regular playback, event playback, external file playback, log playback
Backup Mode	Regular backup, event backup, video clip backup
Streaming Type	Audio/Video, Variable Rate(VBR) , Constant Bit Rate(CBR)
Dual stream	Support
Audio Compression	G.711
Network Interface	2, RJ45 10M/100M self-adaptive LAN port
Protocol	DDNS, EMAIL, UPNP, NTP, DHCP, IP Filter, PPPoE, P2P
Network Users	5 User
Network Bandwidth	80Mbps
P2P	Support, Android/Iphone/Windows Pc
Alarm Input & Output	4 in 1 out
Audio Input & Output	1 RCA in, 1 RCA out, HDMI audio
USB Interface	2x USB2.0 rear port & 1x USB2.0 front port
SATA	2 SATA
Capacity	supports MAX 8TB HDD
Working temperature	±10°C---- 55°C
Operating Humidity	10% ~ 90%
Power Supply	DC12V/3.0A
Power Consumption	10W (without HDD)
Dimension	325mm×245mm×55mm
Net Weight	1.2KG
Gross Weight	1.4KG

Technical Data Sheet



* Product housing specifications are subject to change without prior notice.