

## 2MP+2MP Wi-Fi Smart Linkage Pan-Tilt Dome Camera



## **FEATURES**

- 2+2MP W-Fi Smart Linkage PT Dome Camera
- 4MM+4MM Fixed Lens
- PT Horizontal & Vertical Movement Range Pan 266°, Tilt 90°
- Dual monitoring. One camera for monitoring, One camera for PT detailed monitoring."
- Built-in high-sensitivity Mic and Speaker For Half Duplex Audio Intercom
- Support 10X Digital Zoom
- Can be set 6 preset points favourite locations
- Unique Three Smart Night Vision Modes
- Micro SD Card Up to 256GB & Cloud Storage (Optional)
- Wi-Fi Connection, QR code camera configuration with mobile/PC
- Active defence Siren & Lights
- Customised Voice Recordable massage for Audio Alerts Broadcast
- Area motion detection, Humanoid detection, Push Realtime Notification on the Application"
- Support monitoring: PC / Mobile on TrueCloud
- Compression: H.264/H.265
- Alexa Support



Connection



256GB

SD Card



Resolution





Tracking Compresstion

Video

Auto Human



All Time



Recording



Technical Specifications

Resolution 1920x2160

Lens Bullet: 4mm Fixed Lens

PT Dome: 4mm Fixed Lens

IR LEDs Bullet: 4 Pcs

PT Dome: 6 Pcs

IR LED Distance >30 Meters
White LEDs Bullet: 4 Pcs

PT Dome : 6 Pcs

White LED Distance >20 Meters

Minimum Illumination Color: 0.1 Lux, BW: 0.01 Lux

Day & Night Mode IR / Smart / Full Color

S/N Ratio > 39.1 dB
White Balance Auto
3D-DNR Auto
Mirror/Flip On / Off

Video Streaming Mainstream: 1920x2160@15fps

Substream: 640x720@15fps

Al Features Human Detection

**Motion Detection** 

Built in Speaker

Audio Streaming AAC/G711A

Audio IN Built in MIC

Audio OUT

| Button                         | Device Reset button                                  |
|--------------------------------|--|
| TF /SD Card                    | Support Max 256GB                                    |
| Protocol                       | N1 Protocol  |
| Slots                          | Micro SD Card Slot                                   |
| Connection Mode                | Wi-Fi & Ethernet                                     |
| Wi-Fi standard                 | 802.11b/g/n/a  |
| RJ45 Network Port              | 10-100M adaptive                                     |
| Light Mode                     | LED Flash; 4G Network not Connected                  |
|                                | LED Continue ON; 4G Network Connected                |
| Power Input                    | DC Input 12V – 1A                                    |
| Thunder Prevention             | Standard IEC61000-4-5                                |
| Power Consumption              | ≤15W   |
| Operation Temperature/Humidity | -10 $^{\circ}$ C to +50 $^{\circ}$ C / 30% to 80% RH |
| Storage Temperature/Humidity   | -20°C to +60°C / 20% to 90% RH                       |
| Dimension                      | 167 x 158 x 190mm (L×W×H)                            |
| Housing Type                   | Plastic Housing                                      |
| Weight Net                     | 0.575Kg  |
| Weight Gross                   | 0.555Kg  |

## **Similar Products**



Smart 3MP 4G Cube Camera



Smart 3MP 4G Bullet Camera



Smart 3MP 4G Dome Camera



Smart 3MP 4G Robot Camera



Smart 3MP 4G Mini PT Camera



4G PTZ Camera

<sup>\*</sup> Note: Product specifications are subject to change without prior notice.