

32 inch Floor Mount Non-Touch A9 DSS 2GB/ 16GB T291097-A



FEATURES

- Information can be broadcast, news released, products advertised, etc., digital signage, which is widely used in the fields of entertainment, finance, and traffic.
- Mobile application Based Contain push Over the local Wi-Fi Network
- cloud-based software solution that brings together content management and remote device management capabilities, allowing users to remotely manage hardware settings and troubleshoot issues while effortlessly creating and deploying content with no previous training needed.
- Metallic Body Appearance
 Light weight body with integrative design.
- Variable Materials
 Static and dynamic materials, including pictures, Audio, Video, Scrolling
 Subtitle, PDF, Webpage, Live Video, pop-up pictures, etc.
- Flexible Program Schedule
- > Free schedule and district display of multiple material.
- > Multiple play modes with customization support.
- Centralized Management
- Remotely control and manage one or more screens, such as timed startup/shutdown, quick startup/shutdown, brightness/volume timed adjustment, and screenshot preview.
- > Remote program release and local (USB) program update.
- Organization Permission
- > 5-level organization available for managing materials, programs, terminals, and users.
- Create custom user with precise permission assignment. Multiple permission templates available.
- Multiple Security Safeguards
- > 3-level check of materials, programs, and schedules to prevent mistake release. Screen saver password to protect displaying.
- > Encryption of data storage and transmission to avoid data tampering.
- > With no default password, users can activate and set initial password to auarantee the password safety.
- > DSS Management Software to manage <2000pcs DSS Players





Viewing

Angle



Android



Remote



Power



Technical Specification

DISPLAY

Brightness

Diagonal Size32 inchResolution1366x768Display OrientationPortrait

Screen Type TFT LCD (E-LED Backlight)

Aspect Ratio 16:9

Display Area 697.68(V) × 392.26(H)

LCD Viewing Angle 178°
LCD Refresh Rate(Panel) ≥8.5ms

LED Lifespan 50,000hours,
Working Hours 16x7 Hrs
Contrast Ratio 4000:1(Typ)

≥350cd/**m**[±]10%

COMPUTING

Android OS 9 RAM 2GB

Internal Storage 16GB

CPU Hi352,Quad core, 32Bit, Cortex-A53 CPU,2.30GHz

GPU ARM MaliTM-450

OSD Language English, Arabic, Spanish, French, Italian, Japanese, Portuguese, Russian, etc Video Format Supports H.264/MVC/MPEG1/MPEG2/MPEG4/AVS+(AVS-P16)/VC-1/VP6/8

1080P@60fps Video decoding; support, VP9 10bit, FHD@60fps

Video decoding; Supports low latency video decoding

Audio Format MPEG L1/L2;MP3;AAC_LC;HE_AACV2;LPCM;APE ; FLAC ; Ogg ;

AMR-NB/WB; G.711Supports JPEG hardware decoding, with a maximum

support of 64 million pixels; Support

Picture Format "MJPEG Baseline decoding; Supported formats: 400/420/411/422/422T/444

INPUT PORT

HDMI IN 1

USB 2 (USB2.0)

AUDIO

Dual Speakers 2 x 5W

NETWORK

LAN in(RJ45) 10/100Mbps

Wake-on-LAN Yes

Wi-Fi IEEE802.11a/b/g, 2.4G

POWER

Power Requirements 100V~240V AC, 50/60Hz

Power Consumption 55W
Power Consumption(Standby) 0.5W
Ultra-Quiet Fanless Design Yes

ENVIROMENTAL

Operating Temperature 0°C to 40°C(32°F to 104°F)
Storage Temperature -15° to 55°C(-5°F to 131°F)

Operating Humidity
Storage Humidity
20% to 80% non-condensing humidity
20% to 90% non-condensing humidity

DIMENSION

Product Dimension **Body**: 463.6mm (W) x 1643.3mm (H) x 67.8mm (D),

Floor Stand Set :397.3mm(W) x 702.7mm (H) x 30mm(D)

PACKED CONTENTS

Accessories 1 x Remote Controller, 2 x Key ,1 x Power Cable (Fixed With Device)

